TECHNICAL DATASHEET

WET & PROTECT

1 min. | Up to 3 months | 200/250ml per car

INGENIOUS CAR CARE
Products for professionals

Description:
Cartec Wet & Protect is a hydrophobic spray coating that can be easily applied after washing the car. The product gives the car paint a very deep gloss and provides extreme water beading.

Product benefits:
- Quick to apply spraycoating
- Makes surfaces water-repellent in a very short time
- Gives extremely high contact angle to water and raindrops
- Leaves a protective film on the treated surface
- Highly resistant to acid and alkaline chemicals
- Works well on paintwork, vinyl, PPF and rims

Application:
Cartec Wet & Protect is a “spray & rinse” coating that adheres strongly to the surface after the car has been washed and rinsed. By applying the product to the wet car, Cartec Wet & Protect will spread well and can adhere to the paintwork. Upon rinsing, a very good protective coating, extra deep gloss and a strong water-repellent effect is created which is immediately visible.

Directions for use:
Required pre-treatment:
1. Clean the car with Cartec Twister Comfort *(1407)* and then rinse the car well with a pressure washer.
2. Then wash the whole car with Cartec Cherry Wash *(1208)*. Rinse the shampoo off with clean water.

Treatment
1. Spray the bodywork (and clean rims if desired) from bottom to top with Cartec Wet & Protect. The product can be applied with a sprayer, a pressure pump or a foam lance. Dilute Wet & Protect 1:1 if a pressure pump is used, so that in the end 200-250 ml of pure product gets on the car. Make sure to touch all parts. Do not let the product dry on the surface.
2. Then remove the Cartec Wet & Protect with a pressure washer. Rinse thoroughly again to further activate de product.
3. Dry the surface with a Cartec Aqua Drying Towel XL or a chamois to prevent staining.

Tips & Tricks:
- To avoid staining, always rinse Wet & Protect immediately after application and do not let the product dry on the surface.
- Never use Cartec Wet & Protect in full sunlight or in a hot environment.
- If necessary, apply Cartec Wet & Protect section by section in hot conditions.
- Cartec Wet & Protect contains silicone.
- When using the Cartec foam lance *(3117/60)*, set it on position 2,5. (This for optimal consumption 200-250ml/car at high-pressure cleaner consumption 11ltr/per minute)
- Using a pre-cleaner other than Cartec Twister Comfort may result in a negative effect on the final result.

Supplies:

3114/3

3117/60

3317/50

3009/02

Item codes:

ITEM CODE	CONTENT
1410/1	1L
1410/5	5L
1410/10	10L
1410/20	20L

For safety information, refer to the MSDS.